

40XT

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |

60XT

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

70XT

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

75XT

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

85XT

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

Tire and Wheel Application — Competitive Machine

90XT

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

95XT

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

570LXT

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

1835C

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset | |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|----|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset | |

1838

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset | |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|----|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset | |

1840

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset | |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|----|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset | |

1845

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | | |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2519 | -- | -- | 419 mm (16.5 in) | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 46 mm (1.81 in) | Outset | |

1845B

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|----------------------|-------------|-------------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | | |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2519 | -- | -- | 419 mm (16.5 in) | Wheel | -- | 247.4 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 46 mm (1.81 in) | Outset | |

1845C

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------|------------------------|---------------|----------------|----------------------|-------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | | |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

Tire and Wheel Application — Competitive Machine

(Continued)

1845C (Continued)

Tire and Wheel Application — Competitive Machine

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|-------------|------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Premium Conventional | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2519 | -- | -- | 419 mm (16.5 in) | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 46 mm (1.81 in) | Outset |

D-2060XL

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

DSL801

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

Tire and Wheel Application — Competitive Machine

4515

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|------------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Low Side Wall | | | | | | | | | | |
| 185-9934 | 264 mm (10.4 in) | 521 mm (20.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2523 | -- | 521 mm (20.5 in) | -- | Wheel | 210 mm (8.3 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 27 mm (1.06 in) | Inset |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |

4610

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|------------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Low Side Wall | | | | | | | | | | |
| 185-9934 | 264 mm (10.4 in) | 521 mm (20.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2523 | -- | 521 mm (20.5 in) | -- | Wheel | 210 mm (8.3 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 27 mm (1.06 in) | Inset |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |

4615

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|------------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Low Side Wall | | | | | | | | | | |
| 185-9934 | 264 mm (10 in) | 521 mm (20.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2523 | -- | 521 mm (20.5 in) | -- | Wheel | 210 mm (8.3 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 27 mm (1.06 in) | Inset |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |

Tire and Wheel Application — Competitive Machine

4625

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | | Outset/ Inset |
|----------------------|------------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Low Side Wall | | | | | | | | | | |
| 185-9934 | 264 mm (10.4 in) | 521 mm (20.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2523 | -- | 521 mm (20.5 in) | -- | Wheel | 210 mm (8.3 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 27 mm (1.06 in) | Inset |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |

4635

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | |
| 214-2533 | -- | 419 mm (16.5 in) | -- | Wheel | 210 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 49 mm (1.94 in) | Inset |
| 214-2534 | -- | 419 mm (16.5 in) | -- | Wheel | 210 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 32 mm (1.25 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2533 | -- | 419 mm (16.5 in) | -- | Wheel | 210 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 49 mm (1.94 in) | Inset |
| 214-2534 | -- | 419 mm (16.5 in) | -- | Wheel | 210 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 32 mm (1.25 in) | Inset |

4635XIT

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | | Outset/ Inset |
|-------------|---------------|----------------|------------|----------------------|-------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| Flexport | | | | | | | | | | |
| 226-3736 | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |

Tire and Wheel Application — Competitive Machine

4835

Tire and Wheel Application — Competitive Machine

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Side | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|----------------------|-----------------|--------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | |
| 214-2533 | -- | 419 mm (16.5 in) | -- | Wheel | 210 mm (8.2 in) | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 49 mm (1.94 in) | Inset |
| 214-2534 | -- | 419 mm (16.5 in) | -- | Wheel | 210 mm (8.2 in) | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 32 mm (1.25 in) | Inset |
| 214-2535 | -- | 419 mm (16.5 in) | -- | Wheel | 248 mm (9.7 in) | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Flexport | | | | | | | | | | | |
| 226-3734 | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | 508 mm (20 in) | Left / Right | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | 508 mm (20 in) | Left / Right | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2533 | -- | 419 mm (16.5 in) | -- | Wheel | 210 mm (8.2 in) | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 49 mm (1.94 in) | Inset |
| 214-2534 | -- | 419 mm (16.5 in) | -- | Wheel | 210 mm (8.2 in) | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 32 mm (1.25 in) | Inset |
| 214-2535 | -- | 419 mm (16.5 in) | -- | Wheel | 248 mm (9.7 in) | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |

5625

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Side | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|----------------------|-----------------|--------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | |
| 214-2535 | -- | 419 mm (16.5 in) | -- | Wheel | 248 mm (9.7 in) | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Flexport | | | | | | | | | | | |
| 226-3736 | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | -- | Left / Right | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | -- | Left / Right | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2535 | -- | 419 mm (16.5 in) | -- | Wheel | 248 mm (9.7 in) | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |

5635

| Mount | | | | | | | | | | | |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset |
| XD | | | | | | | | | | | |
| 214-2535 | -- | -- | 419 mm (16.5 in) | -- | Wheel | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |
| 222-3962 | 777 mm (31 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 785 mm (31 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2535 | -- | -- | 419 mm (16.5 in) | -- | Wheel | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |

6620

| Mount | | | | | | | | | | | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

6625

| Mount | | | | | | | | | | | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

6635

| Mount | | | | | | | | | | | |
|-------------|------------------------|----------------|------------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset |
| XD | | | | | | | | | | | |
| 214-2535 | -- | -- | 419 mm (16.5 in) | Wheel | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |
| 222-3962 | 777 mm (31 in) | 254 mm (10 in) | 419 mm (16.5 in) | Tire | -- | -- | -- | -- | -- | -- | -- |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

Tire and Wheel Application — Competitive Machine

(Continued)

6635 (Continued)

Tire and Wheel Application — Competitive Machine

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|-------------|------|-----------------|----------------------|---------------|---------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 785 mm (31 in) | 254 mm (10 in) | 419 mm (16.5 in) | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2535 | -- | -- | 419 mm (16.5 in) | Wheel | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |
| 242-0620 | -- | 355 mm (14 in) | 444 mm (17.5 in) | Tire | -- | -- | -- | -- | -- | -- | -- |

1300

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|----------------------|-------------|------------|--------|------------------|
| | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- |

1450

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|----------------------|-------------|------------|--------|------------------|
| | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- |

2250

| Part Number | Tire Assembly Diameter | Tire Width | Side | Wheel Diameter | Description | Mount | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|--------------|----------------|----------------------|----------------------|---------------|---------------|-----------------|------------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | Left / Right | 279 mm (11 in) | Tire/ Wheel Assembly | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | Left / Right | 279 mm (11 in) | Tire/ Wheel Assembly | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

Tire and Wheel Application — Competitive Machine

190

Tire and Wheel Application — Competitive Machine

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |

240

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2530 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 24 mm (0.94 in) | Outset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2530 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 24 mm (0.94 in) | Outset | |

Tire and Wheel Application — Competitive Machine

250

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

260

Tire and Wheel Application — Competitive Machine

| Mount | | | | | | | | | | | | |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|-------------|----------------|----------------------|---------------|---------------|-----------------|--------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/Inset |
| XD | | | | | | | | | | | | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 242-0620 | -- | 355 mm (14 in) | 444 mm (17.5 in) | -- | Tire | -- | -- | -- | -- | -- | -- | -- |
| Premium Conventional Flotation | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- |

270

| Mount | | | | | | | | | | | | |
|----------------------|------------------------|----------------|------------------|------------|-------------|------|-------------|----------------------|-------------|------------|--------|--------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/Inset |
| Premium Conventional | | | | | | | | | | | | |
| 242-0620 | -- | 355 mm (14 in) | 444 mm (17.5 in) | -- | Tire | -- | -- | -- | -- | -- | -- | -- |

310SE

| Mount | | | | | | | | | | | | |
|-------------|------------------------|---------------|----------------|------------|----------------------|-------------|----------------|----------------------|---------------|---------------|-----------------|--------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/Inset |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

675

| Mount | | | | | | | | | | | | |
|----------------------|----------------|------------------|------------|-------------|------|-----------------|----------------------|---------------|-----------------|-----------------|--------------|--|
| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/Inset | |
| XD | | | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset | |

4475

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

5575

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

6675

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

Tire and Wheel Application — Competitive Machine

7775

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | |
| 214-2515 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | |
| 187-1279 | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | |
| 226-3736 | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

8875

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|--------------------------------|------------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | |
| 214-2517 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| 222-3963 | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | |
| 187-3230 | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | |
| 226-3734 | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| Premium Conventional | | | | | | | | | | | |
| 185-9933 | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | |
| 214-2517 | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | |
| 199-5440 | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | |

S175

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|-------------|-------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| Flexport | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |

S185

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|-------------|-------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| Flexport | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |

742

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

743

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|--------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |

(Continued)

Tire and Wheel Application — Competitive Machine

743 (Continued)

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

751

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|-------------|---------------|---------------|----------------------|-----------------|---------------|
| | | | | | | | Bolt Circle | Pilot Hole | Number of Bolt Holes | | |
| Flexport | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | 14 mm (0.55 in) | Inset |

753

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Ply Rating | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|----------------------|------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | Wheel | -- | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | Tire | 10 | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | Tire/ Wheel Assembly | -- | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | -- | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | -- | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | Tire | 8 | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | -- | 419 mm (16.5 in) | Wheel | -- | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

Tire and Wheel Application — Competitive Machine

753L

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

Tire and Wheel Application — Competitive Machine

763

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

773

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |

(Continued)

773 (Continued)

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

843

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset |
| Premium Conventional Flotation | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- |

853

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|--------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

(Continued)

853 (Continued)

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|-------------|------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

853H

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

863

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

(Continued)

Tire and Wheel Application — Competitive Machine

863 (Continued)

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|-------------|------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

863G

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | | Inset |

873

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

883

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

7753

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

8853

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2518 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 36 mm (1.42 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

Tire and Wheel Application — Competitive Machine

920

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

930A

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

940

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.4 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.4 in) | Inset |

960

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|--------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2519 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 46 mm (1.81 in) | Outset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |

(Continued)

960 (Continued)

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2519 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 46 mm (1.81 in) | Outset | |

2042

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | | Inset |

2044

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|-------------|-----------------|---------------|
| Flexport | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 14 mm (0.55 in) | Inset |

2050

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | | Inset |

2054

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | | Inset |

Tire and Wheel Application — Competitive Machine

2060

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | |
| 214-2535 | -- | -- | 419 mm (16.5 in) | Wheel | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | Tire | -- | -- | -- | -- | -- | -- | -- |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| Premium Conventional | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2535 | -- | -- | 419 mm (16.5 in) | Wheel | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | -- | Inset |

2070

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

2074

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

Tire and Wheel Application — Competitive Machine

L-465

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

L-553

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

L-555

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

Tire and Wheel Application — Competitive Machine

L-565

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|---------------|----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2515 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.4 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.4 in) | Inset |

L-585

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

L-781

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset |
| Premium Conventional Flotation | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- |

Tire and Wheel Application — Competitive Machine

L-783

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

Tire and Wheel Application — Competitive Machine

L-785

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left/ Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

L-865

Tire and Wheel Application — Competitive Machine

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

L-885

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |

L-985

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2517 | -- | 419 mm (16.5 in) | -- | Wheel | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset |
| 222-3963 | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9933 | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2517 | -- | 419 mm (16.5 in) | -- | Wheel | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset |
| 242-0620 | 355 mm (14 in) | 444 mm (17.5 in) | -- | Tire | -- | -- | -- | -- | -- | -- |

LS-140

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|--------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

LS-150

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|----------------|--------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.4 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.4 in) | Inset |

Tire and Wheel Application — Competitive Machine

LS-160

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

LS-170

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

LS-180

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

(Continued)

LS-180 (Continued)

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|-------------|------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset |
| Premium Conventional Flotation | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- |

LS-190

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset |
| 242-0620 | -- | 355 mm (14 in) | 444 mm (17.5 in) | -- | Tire | -- | -- | -- | -- | -- | -- | -- |
| Premium Conventional Flotation | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- |

LX-465

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | |
| XD | | | | | | | | | | | | |
| 214-2514 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

Tire and Wheel Application — Competitive Machine

LX-485

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|-----------------|---------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- |
| Premium Conventional | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset |

LX-565

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Flexport | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

LX-585

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset |

Tire and Wheel Application — Competitive Machine

LX-665

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

Tire and Wheel Application — Competitive Machine

LX-685

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

LX-865

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------|------------------------|----------------|------------------|------------|----------------------|--------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

(Continued)

LX-865 (Continued)

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|-------------|------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

LX-885

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

LX-985

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

Tire and Wheel Application — Competitive Machine

561

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

584

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 777 mm (30.6 in) | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-1279 | 787 mm (31 in) | 127 mm (5 in) | 177 mm (7 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 785 mm (30.9 in) | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

784

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|--------------------------------|------------------------|------------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| XD | | | | | | | | | | | | | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2517 | -- | -- | 419 mm (16.5 in) | -- | Wheel | -- | 247 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 28 mm (1.12 in) | Inset | |
| Premium Conventional Flotation | | | | | | | | | | | | | |
| 199-5440 | 838 mm (33 in) | 393 mm (15.5 in) | 419 mm (16.5 in) | 12 | Tire | -- | -- | -- | -- | -- | -- | -- | |

Tire and Wheel Application — Competitive Machine

1300C

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |

1500C

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |

1500D

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | -- | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset | |

1700CX

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

2300

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | | Offset | Outset/ Inset |
|-------------|------------------------|---------------|----------------|------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|--------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | | |
| Flexport | | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | -- | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

T-103

| | | | | | | | | | | | Mount | | |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|-----------------|--------------|--------------------|-------|--|--|
| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Outset/Inset | Outside Diameter | | | |
| XD | | | | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | Inset | -- | | | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | 777.2 mm (30.6 in) | | | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | 784.4 mm (30.9 in) | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 6 | 152 mm (6 in) | 117 mm (4.6 in) | Inset | -- | | | |

T-133

| | | | | | | | | | | | Mount | | |
|----------------------|----------------|------------------|------------|-------------|-----------------|------|----------------------|---------------|-----------------|-----------------|--------------|--|--|
| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Side | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/Inset | | |
| XD | | | | | | | | | | | | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | -- | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset | | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | -- | | |
| 214-2514 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | -- | 6 | 152 mm (6 in) | 117 mm (4.6 in) | 10 mm (0.38 in) | Inset | | |

T-173

| | | | | | | | | | | | Mount | | |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|--------------|--|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/Inset | |
| XD | | | | | | | | | | | | | |
| 214-2520 | -- | -- | 419 mm (16.5 in) | -- | -- | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 57 mm (2.25 in) | Outset | |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| Extreme Duty Solid | | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset | |
| Premium Conventional | | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- | |
| 214-2520 | -- | -- | 419 mm (16.5 in) | -- | -- | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 57 mm (2.25 in) | Outset | |

Tire and Wheel Application — Competitive Machine

T-203

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2520 | -- | -- | 419 mm (16.5 in) | -- | -- | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 57 mm (2.25 in) | Outset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2520 | -- | -- | 419 mm (16.5 in) | -- | -- | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 57 mm (2.25 in) | Outset |

T-233

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2520 | -- | -- | 419 mm (16.5 in) | -- | -- | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 57 mm (2.25 in) | Outset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2520 | -- | -- | 419 mm (16.5 in) | -- | -- | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 57 mm (2.25 in) | Outset |

T-243

| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Ply Rating | Description | Side | Wheel Width | Mount | | | Offset | Outset/ Inset |
|----------------------|------------------------|----------------|------------------|------------|----------------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|
| | | | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| XD | | | | | | | | | | | | |
| 214-2520 | -- | -- | 419 mm (16.5 in) | -- | -- | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 57 mm (2.25 in) | Outset |
| 222-3963 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 14 | Tire | -- | -- | -- | -- | -- | -- | -- |
| Extreme Duty Solid | | | | | | | | | | | | |
| 187-3230 | 838 mm (33 in) | 152 mm (6 in) | 203 mm (8 in) | -- | Tire/ Wheel Assembly | Left/ Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 51 mm (2 in) | Outset |
| Premium Conventional | | | | | | | | | | | | |
| 185-9933 | -- | 304 mm (12 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | -- |
| 214-2520 | -- | -- | 419 mm (16.5 in) | -- | -- | -- | 248 mm (9.7 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 57 mm (2.25 in) | Outset |

Tire and Wheel Application — Competitive Machine

T-173

| | | | | | | | | | | | Mount | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|---------------|------------------|--|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Outset/ Inset | Outside Diameter | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | Inset | 838 mm (33 in) | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | Inset | 838 mm (33 in) | |

T-173HL

| | | | | | | | | | | | Mount | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|--|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

T-173HLS

| | | | | | | | | | | | Mount | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|--|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

T-175

| | | | | | | | | | | | Mount | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|--|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

T-233HD

| | | | | | | | | | | | Mount | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|--|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset | |
| Flexport | | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset | |

Tire and Wheel Application — Competitive Machine

T-245

| | | | | | | | Mount | | | | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|----------------|----------------------|---------------|---------------|-----------------|---------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset |
| Flexport | | | | | | | | | | | |
| 226-3734 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |
| 226-3735 | 838 mm (33 in) | 152 mm (6 in) | 279 mm (11 in) | Tire/ Wheel Assembly | Left / Right | 508 mm (20 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 27 mm (1.05 in) | Inset |

2SDK7

| | | | | | | | Mount | | | | |
|-------------|------------------------|---------------|----------------|----------------------|--------------|-------------|----------------------|---------------|---------------|-----------------|---------------|
| Part Number | Tire Assembly Diameter | Tire Width | Wheel Diameter | Description | Side | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset |
| Flexport | | | | | | | | | | | |
| 226-3736 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |
| 226-3737 | 787 mm (31 in) | 152 mm (6 in) | 254 mm (10 in) | Tire/ Wheel Assembly | Left / Right | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 14 mm (0.55 in) | Inset |

2SDK8

| | | | | | | Mount | | | | | |
|----------------------|----------------|------------------|------------|-------------|-----------------|----------------------|---------------|---------------|-----------------|---------------|--|
| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Number of Bolt Holes | Bolt Circle | Pilot Hole | Offset | Outset/ Inset | |
| XD | | | | | | | | | | | |
| 214-2515 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |
| 222-3962 | 254 mm (10 in) | 419 mm (16.5 in) | 10 | Tire | -- | -- | -- | -- | -- | -- | |
| Premium Conventional | | | | | | | | | | | |
| 185-9932 | 254 mm (10 in) | 419 mm (16.5 in) | 8 | Tire | -- | -- | -- | -- | -- | -- | |
| 214-2515 | -- | 419 mm (16.5 in) | -- | Wheel | 209 mm (8.2 in) | 8 | 203 mm (8 in) | 152 mm (6 in) | 10 mm (0.38 in) | Inset | |

Tire and Wheel Application — Competitive Machine

Narrow Configuration

| Part Number | Tire Width | Wheel Diameter | Ply Rating | Description | Wheel Width | Mount | | | Offset | Outset/Inset |
|-------------|---------------|----------------|------------|----------------------|-------------|----------------------|---------------|---------------|-----------------|--------------|
| | | | | | | Number of Bolt Holes | Bolt Circle | Pilot Hole | | |
| 238-7738 | 177 mm (7 in) | 381 mm (15 in) | 6 | Tire/ Wheel Assembly | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 29 mm (1.15 in) | Inset |
| 238-7739 | 177 mm (7 in) | 381 mm (15 in) | 6 | Tire/ Wheel Assembly | -- | 8 | 203 mm (8 in) | 152 mm (6 in) | 29 mm (1.15 in) | Inset |
| 238-7740 | 177 mm (7 in) | 381 mm (15 in) | 6 | Tire | -- | -- | -- | -- | -- | -- |

Tire and Wheel Application — Competitive Machine